

# Influences of Gasoline Fuels on Waste Heat Recovery Potentiality of a Spark Ignition Engine

I. M. Yusri<sup>1\*</sup>, R. Mamat<sup>2</sup>, W. H. Azmi<sup>2</sup>, Omar I. Awad<sup>1</sup>, M. F. Othman<sup>1</sup> and S. M. Rosdi<sup>1</sup>

<sup>1</sup>Faculty of Mechanical Engineering, Universiti Malaysia Pahang, 26600 Pekan, Pahang Malaysia

<sup>2</sup>Automotive Engineering Centre, Universiti Malaysia Pahang, 26600 Pekan, Pahang Malaysia;  
m.yusri890@gmail.com

## Abstract

**Objectives:** In this study, evaluation of the potential of energy recovery in spark ignition engine using RON 95 gasoline fuels. **Methods:** The engine has been operated at a single engine speeds of 3500 RPM with 50% of Wide Throttle Open (WTO). The potential of energy recovery was measured by means of engine effective power, Water Heat Losses (WHL) and Exhaust Heat Losses (EHL). **Findings:** Comparative analysis of the experimental results showed an improvement of 1.16%, 2.12% and 3.08% in EHL at 75°C, 50°C and 25°C, respectively, by taking 120°C as the reference temperature of EHL. The results of the contour plot showed that a trade-off between the WHL and EHL. **Conclusion:** Higher proportions of energy losses can be utilised by considering both WHL and EHL.

**Keywords:** Exhaust Heat Losses, Effective Power, Water Heat Losses (WHL)

\*Author for correspondence